

# HP Color LaserJet Enterprise CP5520 Printer series

Ideal for workgroup or fleet printing in managed enterprise, public sector or medium-sized businesses, wanting an easy-to-use, colour printer with superior paper capacity, that can handle general office documents and wide-format output.









### Enable colour printing from postcards to posters.

- Expand your business options: print presentations, high-impact reports and marketing materials on a wide range of media types and sizes, from postcard to SRA3.
- Produce high-volume print jobs without frequent paper changes, with a paper capacity up to 2,350 sheets[1].
- Improve efficiency: HP Advanced Auto Media Sensing automatically adjusts settings according to paper type and size, for best printing results.
- Increase productivity and versatility with automatic two-sided printing[2].

# Achieve great colour prints with uncompromised

- · Save time with fast printing: documents are printed at up to 30 ppm A4.
- Get a first page out in 10 seconds from power save mode with no-wait Instant-on Technology.
- Enjoy consistent print quality: get accurate high-quality, glossy text, graphics, and images automatically with HP EasyColor and HP ImageREt.
- Use Original HP LaserJet print cartridges with HP ColorSphere toner to achieve sharp contrast, precise drawings and vibrant images from a broad colour aamut.

## Count on a printer that is easy to use and manage.

- Print from anywhere, anytime, with a smartphone, notebook PC or other mobile device, using HP ePrint[3].
- Expand your security options and easily integrate enterprise-ready gigabit networking into your printing fleet.
- Supervise printing fleets remotely using HP Web Jetadmin and control colour printing usage and costs with HP Color Access Controls.
- Print quickly and easily just plug a Flash drive into the USB port and print. Keep sensitive data safe with HP High-Performance Secure Hard Disk[4].

#### **ecohighlights**

- Reduce energy use by up to 50% with Instant-on Technology[1].
- Avoid reprints with the consistency of Original HP toners plus HP Professional Color Technologies.
- Reduce paper use by up to 50% using automatic two-sided printing[2].
- Convenient cartridge recycling in 53 countries.

#### **ENERGY STAR® Qualified**

[1] Energy savings based on HP testing using the ENERGY STAR® programme's Typical Electricity Consumption (TEC) method on HP LaserJet products with Instant-on Technology vs. top competitive models as of March 2009.

[2] Automatic two-sided printing is available on the dn and xh models only. Please recycle your computer hardware and printing supplies. HP assel management and recycling services make responsible disposal easy.

<sup>[1]</sup> Optional 500-sheet paper tray is available and sold separately for the n and dn models

<sup>[2]</sup> Automatic two-sided printing is available on the dn and xh model only.
[3] May require an Internet connection to the printer. Feature works with any Internet and e-mail-capable device and may require a firmware upgrade. For details, vw.hp.com/go/ePrintCenter.

<sup>[4]</sup> Optional HP High-Performance Secure Hard Disk is available and sold separately for the n and dn models

## Product walkground

HP Color LaserJet Enterprise CP5520 Printer series

- 1 Intuitive control panel with 4 line color display
- 2 300-sheet top output bin
- 3 One-door access to the easy to install print cartridges
- 4 100-sheet multipurpose tray recognizes paper sizes up to  $\ensuremath{\mathsf{SRA3}}$
- 5 250-sheet tray 2
- 6 500-sheet tray 3
- 7 Three 500-sheet input trays with print stand for 2,350-sheet total input capacity
- 8 USB 2.0 port for walk up printing
- 9 Built-in automatic two-sided printing
- 10 Hi-Speed USB 2.0 port for direct connection to printer
- 11 HP Jetdirect Gigabit Ethernet embedded print server
- 12 1 GB RAM and an 800 MHz processor
- 13 120 GB HP Encrypted High Performance Hard Disk
- 14 One open EIO slot



## Series at a glance



#### HP Color LaserJet Enterprise CP5525n Printer

- HP Color LaserJet Enterprise CP5525n Printer: print speed of up to 30 ppm colour and 30 ppm black
- up to 600 x 600 dpi effective output quality with HP ImageREt 3600
- 1 GB RAM
- 800 MHz processor
- 1 Hi-Speed USB 2.0 port
- 1 USB 2.0 port for walk up printing
- 8 GB HP High-Performance Secure Hard Disk
- HP Jetdirect Gigabit Ethernet embedded print server
- 100-sheet multipurpose tray
- 250-sheet input tray 2
- 500-sheet input tray 3



#### HP Color LaserJet Enterprise CP5525dn Printer

 HP Color LaserJet Enterprise CP5525dn Printer: as CP5525n model plus automatic two-sided printing.



#### HP Color LaserJet Enterprise CP5525xh Printer

- HP Color LaserJet Enterprise CP5525xh Printer: as CP5525n model plus
- two-sided printing
- additional 3 x 500-sheet input trays 4 and 5 and 6
- 120 GB HP High-Performance Secure Hard Disk

#### Recommended accessories



**HP Color LaserJet 500-sheet** 

Enhance productivity with a

simple-to-install paper tray

pages without reloading

different types of paper

paper and keep two

that allows you to print more

CE860A

**Paper Tray** 

loaded.





#### 18019A **HP Secure High Performance** EIO Hard Disk

Securing your business means protecting information. With the HP High-Performance Secure EIÖ Hard Disk with a Kensington-style lock, you can easily help secure valuable data at rest on your HP printer or MFP and still achieve optimal

performance.



# 18021A

## HP Jetdirect ew2500 802.11b/g Wireless Print

Get the best of both worlds share HP printers and multifunction products via wireless or wired networks Send and print documents protected by IPSec, 802.11x and several encryption options. Enjoy easy installation, set up and management.



#### 17934G

#### HP Jetdirect 620n Fast **Ethernet Print Server**

industry-leading performance, the HP . Jetdirect 620n Fast Ethernet Internal Print Server enables businesses to share HP printers with EIO slots, easily and affordably across the network and the Internet.

With advanced security and



#### 17961G

#### HP Jetdirect 635n IPv6/IPsec **Print Server**

Share supported peripherals over your network with one of the first Gigabit EIO print servers to support IPv6, IPv4 and IPsec. Rely on advanced network technology and security, and get data transmission at Gigabit speeds (up to 1000 Mbit per second)



### 18007G

## HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print

The HP Jetdirect 690n Wireless 802.11g Print Server provides both wireless or wired connectivity. Get advanced authentication and encryption through IPsec. Enjoy broad compatibility, robust security and easy management in the IT environment.

## Ordering information



Accessories

CF860A

J8019A

#### HP Color LaserJet Enterprise CP5525n Printer (CE707A)

HP Color LaserJet CP5525n printer; Print cartridges (1 each black, cyan, magenta, yellow); HP Color LaserJet 250-sheet Paper Tray 2; HP Color LaserJet 500-sheet Paper Tray 3; CDs containing device software and electronic User's Guide; Documentation (including Getting Started Guides); power cord



#### HP Color LaserJet Enterprise CP5525dn Printer (CE708A)

HP Color LaserJet CP5525dn printer; Print cartridges (1 each black, cyan, magenta, yellow); HP Color LaserJet 250-sheet Paper Tray 2; HP Color LaserJet 500-sheet Paper Tray 3; CDs containing device software and electronic User's Guide; Documentation (including Getting Started Guides); power cord



#### HP Color LaserJet Enterprise CP5525xh Printer (CE709A)

HP Color LaserJet CP5525xh printer, Print cartridges (1 each black, cyan, magenta, yellow); HP Color LaserJet 250-sheet Paper Tray 2; HP Color LaserJet 500-sheet Paper Tray 3; HP Color LaserJet 3 x 500-sheet Paper Feeder and Stand; 120 GB secure hard disk drive; CDs containing device software and electronic User's Guide; Documentation (including Getting Started Guides); power cord

# Accessories, Supplies and Support

HP Color LaserJet 500-sheet Paper Tray

HP Secure High Performance EIO Hard Disk

	5
Supplies	
CE270A	HP Color LaserJet CE270A Black Print Cartridge
	Average continuous Black Cartridge yield 13,500
	standard pages. Declared yield value in accordance
	with ISO/IEC 19798 in continuous printing.
CE271A	HP Color LaserJet CE271A Cyan Print Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 15,000 standard pages. Declared yield
	value in accordance with ISO/IEC 19798 in continuous
	printing.
CE272A	HP Color LaserJet CE272A Yellow Print Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 15,000 standard pages. Declared yield
	value in accordance with ISO/IEC 19798 in continuous
	printing.
CE273A	HP Color LaserJet CE273A Magenta Print Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 15,000 standard pages. Declared yield
	value in accordance with ISO/IEC 19798 in continuous
	printing.
CE980A	HP Color LaserJet CE980A Toner Collection Unit
	Up to 150,000 pages
CE977A	HP Color LaserJet CE977A 110V Fuser Kit
	Up to 150,000 pages

CE978A	HP Color LaserJet CE978A 220V Fuser Kit		
	Up to 150,000 pages		
CE979A	HP Color LaserJet CE979A Transfer Kit		
	Up to 150,000 pages		

#### Connectivity

J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server
J7934G	HP Jetdirect 620n Fast Ethernet Print Server
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
J8007G	HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print
	Server

#### Service & support

1 year.

UV276E HP Care Pack, 4 Hour Response Time 13x5 Color Laserlet Enterprise CP5520 Printer Hardware Support, 3 years UX964E HP Care Pack, Next Business Day Color LaserJet Enterprise CP5520 Printer Hardware Support, 3 years

UV280E HP Care Pack, Next Business Day Color LaserJet Enterprise CP5520 Printer Hardware Support, 4 years

UV279E HP Care Pack, Next Business Day Color LaserJet Enterprise CM4540 MFP Hardware Support, 5 years

**UV269PE** HP Care Pack, Post Warranty Next Business Day Color LaserJet Enterprise CP5520 Printer Hardware Support, 1 year UV268PE HP Care Pack, Post Warranty Next Business Day Color LaserJet Enterprise CP5520 Printer Hardware Support, 2 years UV271PE HP Care Pack, Post Warranty 4 Hour Response Time 13x5 Color LaserJet Enterprise CP5520 Printer Hardware Support, For a complete list of supplies, accessories and services, please refer to http://www.hp.com

Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grow your business—with expert support that's affordable, personal, and tailored to your needs through HP Care Pack Services.



# **Technical specifications**

Print technology	Laser						
Print speed	First page out Black: As fast as 10 sec, Colour: As fast as 10 sec						
•	A4 Black: Up to 30 ppm, Colour: Up to 30 ppm						
			For more information see http://www.hp.com/go/	printerclaims. Exact speed varies depending on the			
	system configuration, software application, driver, and document complexity.						
Processor	800 MHz, Intel® X86-VR						
Memory	1 GB, Not expandable, Hard disk capacity						
Print resolution	Flack: Up to 600 x 600 dpi						
	Colour: Up to 600 :						
Print quality	The management of the manageme						
Printer languages	HP PCL 5, HP PCL 5c (HP PCL 5c driver available from the Web only), HP Postscript level 3 emulation, native PDF printing (v1.4)						
Typefaces/fonts	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); additional font solutions available via third-part						
Typeraces/ IOIIIs	flash memory cards						
Duty cycle (monthly, A4)	Up to 120000 page						
Recommended Monthly Page Volume	2500 to 10,000						
, ,	2500 to 10,000 top: 5 mm, left: 5 mm, right: 5 mm, bottom: 5 mm						
Print margins		-	w.t.	<u> </u>			
Media handling	Input	Capacity	Weight	Size			
	Tray 1	sheets: 100; transparencies: 50; envelopes: 10	60 to 220 g/m <sup>2</sup>	A3; A4; A5; B4 (JIS); B5; B5 (JIS); C5; DL; SRA3			
	Tray 2	sheets: 250; transparencies: 50	60 to 120 g/m² plain papers, up to 160 g/m²	A3; A4; A5; B4 (JIS); B5; B5 (JIS); C5; DL			
	T 2	sheets: 500	coated papers 60 to 120 g/m² plain papers, up to 160 g/m²	A 2 . A 4 . A 5 . D 4 (IIC) . D 5 . D 5 (IIC) . C 5 . D 1			
	Tray 3	sneets: 500	coated papers	A3; A4; A5; B4 (JIS); B5; B5 (JIS); C5; DL			
	Duplex printing:	CP5525n: Manual (driver support provided);	60 to 120 g/m <sup>2</sup> plain papers, up to 160 g/m <sup>2</sup>	A3; A4; B4; B5 (JIS); SRA3			
	Duplex prinning.	CP5525dn: Automatic (standard); CP5525xh:	coated papers	A3, A4, B4, B3 (JIS), SKA3			
		Automatic (standard)	codied papers				
	Output:	Sheets: Up to 300 sheets. Envelopes: Up to 40 er	nvelones Transparencies: Un to 300 sheets				
Media types		glossy, heavy, heavy glossy, high gloss images, inter		ole cardetack transparancies			
Interface and connectivity		nernet, Gigabit Ethernet, IPv6, BiDi, Hi-Speed USB 2.1		els, carasiock, iransparencies			
				-1 C 2000 221-1 1 (4 l-1 1 2000 D2			
Operating systems compatibility	Windows® 7 32-bit and 64-bit, Windows Vista® 32-bit and 64-bit, Microsoft® Windows® XP 32-bit or 64-bit (SP2 or higher), Server 2008 32-bit and 64-bit, and 2008 R2						
				/			
	Edition, Server 200	3 32-bit and 64-bit, Citrix® and Windows® Termina	Il Services (see whitepapers at http://www.hp.com/	go/upd, Documentation tab); Novell® (see			
	Edition, Server 2003 http://www.novell.com	3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h	Il Services (see whitepapers at http://www.hp.com/ http://www.hplip.net); UNIX, SAP device types				
	Edition, Server 200: http://www.novell.o Optional: Latest driv	3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h	Il Services (see whitepapers at http://www.hp.com/ http://www.hplip.net); UNIX, SAP device types	go/upd, Documentation tab); Novell® (see s to the Internet, see support flyer that came in printer			
Network operating systems compatibility	Edition, Server 200: http://www.novell.o Optional: Latest driv box	13 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at	Il Services (see whitepapers at http://www.hp.com/ http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no acces	s to the Internet, see support flyer that came in printer			
Network operating systems compatibility	Edition, Server 200: http://www.novell.e Optional: Latest driv box Windows® 7 32-bit	13 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mindows Vista® 32-bit and 64-bit an	Il Services (see whitepapers at http://www.hp.com/s http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/djcp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or highe	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2			
Network operating systems compatibility	Edition, Server 200 http://www.novell.c Optional: Latest driv box Windows® 7 32-bit Edition, Server 200	13 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v 10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mindows Wista® 32-bit and 64-bit, Citrix® and Windows® Termina	Il Services (see whitepapers at http://www.hp.com/s ttp://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/dicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or highe all Services (see whitepapers at http://www.hp.com/s	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2			
	Edition, Server 200: http://www.novell. Optional: Latest driv box Windows® 7 32-bit Edition, Server 200: http://www.novell.	13 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h	Il Services (see whitepapers at http://www.hp.com/eitp://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no accestrosoft® Windows® XP 32-bit or 64-bit (SP2 or higher Il Services (see whitepapers at http://www.hp.com/eitp://www.hplip.net); UNIX, SAP device types	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 ggo/upd, Documentation tab); Novell® (see			
Network operating systems compatibility  Minimum system requirements	Edition, Server 200: http://www.novell.d Optional: Latest driv box Windows® 7 32-bit Edition, Server 200: http://www.novell.d Windows® 7; Windows® 7;	33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hvers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33-2-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hdows Vista®; Microsoft® Windows® XP SP2 or high	al Services (see whitepapers at http://www.hp.com/eitp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no access crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/eitp://www.hplip.net); UNIX, SAP device types er, Server 2003, Server 2008; OS Compatible hard	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see			
	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cows.micross.py. http://www.micross.http://www.micross.py.	33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprintl); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprintl); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard	al Services (see whitepapers at http://www.hp.com/eitp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no access crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/eitp://www.hplip.net); UNIX, SAP device types er, Server 2003, Server 2008; OS Compatible hard	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see			
Minimum system requirements	Edition, Server 200. http://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.microschttp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp://www.apple.cohtp.	33-bit and 64-bit, Citrix® and Windows® Termina com/jprint); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit, Citrix® and Windows® Termina com/jprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high offi.com system requirements; 220 MB available hard com; 150 MB free hard disk space	Il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/cljcp5525. If no accestrosoft® Windows® XP 32-bit or 64-bit (SP2 or higher Il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hardisk space, Mac OS X v10.4 or higher; Operating	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see			
Minimum system requirements Software	Edition, Server 200. http://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.novell.cohtp://www.nicrose.http://www.apple.coht	33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hevers for all supported operating systems available at the and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hedows Vista®; Microsoft® Windows® XP SP2 or high officom system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.lip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no acces trosoft® Windows® XP 32-bit or 64-bit (SP2 or higher II Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types let, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 20/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements	Edition, Server 200. http://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.microschttp://www.apple.cohttp://	33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7 ju	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher Il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types lear, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher, Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, He	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 20/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel	Edition, Server 200. http://www.novell.coptional: Latest drivbox Windows® 7 32-bit Edition, Server 200. http://www.novell.com/strp://www.microschttp://www.microschttp://www.apple.com/strp://www.appl	33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF sur, graphical and text, LCD control panel display; 7 jeady); Enhanced help with animated graphics; Walker	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.icp.netl); UNIX, SAP device types http://www.hp.icp.netl); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl); UNIX, SAP device types eter, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher, Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 20/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel  Printer management	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.com/server 200. http://www.microschttp://www.microschttp://www.apple.com/serversand ins 5.2 cm, 4-line colou (Attention, Data, Re-	33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, ICD control panel display; 7 jeady); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less tha	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/support/clicp5525. If no acces http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher Il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ser, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users	st to the Internet, see support flyer that came in printer st, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel	Edition, Server 200. http://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.nicross.http://www.micross.http://www.apple.cohttp:/	332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h vers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see h dows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7 ju addy); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/support/clicp5525. If no acces http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher Il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ser, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 20/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software Control panel  Printer management Power	Edition, Server 200. http://www.novell.cohthis/www.novell.cohthis/www.novell.cohthis/www.novell.cohthis/www.novell.cohthis/www.nicroschttp://www.nicroschttp://www.apple.cohthis/www.apple.cohth	33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at the and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33-2bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high officom system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7 judy); Enhanced help with animated graphics; Walkstatus Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (consumption (TEC) 5.644 kWh/Week	all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/cljcp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heury USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts	st to the Internet, see support flyer that came in printer st, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel  Printer management	Edition, Server 200. http://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.nicrose.http:/	13 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hevers for all supported operating systems available at the and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 13 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hedows Vista®; Microsoft® Windows® XP SP2 or high offic.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7 juddy); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (consumption (TEC) 5.644 kWh/Week	all Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/support/clicp5525. If no access trosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types lear, Server 2003, Server 2008; OS Compatible hard clisk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watt 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm	st to the Internet, see support flyer that came in printer st, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel  Printer management  Power  Dimensions (w x d x h)	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cow.novell.com/server 200. http://www.nicroschttp:/	33-2-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see holdows Vista®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF sur, graphical and text, LCD control panel display; 7 igrady); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (possumption (TEC) 5.644 kWh/Week PS525n: 544 x 586 x 465 mm; CP5525dn: 945 x 767 x 822 mm; CP5525dn: 995 x 767 x 82	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hp.com/support/clipc5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher II Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types etc., Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher, Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm	st to the Internet, see support flyer that came in printer st, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel  Printer management  Power  Dimensions (w x d x h)	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.com/strp://www.microschttp://www.microschttp://www.microschttp://www.apple.com/steritorion.com/strp://www.apple.com/s	33-2-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at the and 64-bit; Windows Vista® 32-bit and 64-bit; Mica 33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, ICD control panel display; 7 iprady); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (onsumption (TEC) 5.644 kVh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 58 nr: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 825	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hp.com/support/clipc5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher II Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types etc., Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher, Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm	st to the Internet, see support flyer that came in printer st, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see:			
Minimum system requirements  Software  Control panel  Printer management  Power  Dimensions (w x d x h)  Weight	Edition, Server 200. http://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.microschttp://www.microschttp://www.microschttp://www.apple.cohttp://w	332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at the and 64-bit; Windows Vista® 32-bit and 64-bit; Windows Vista® 32-bit and 64-bit; Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high oft.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7 ig vady); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week PS525n: 544 x 586 x 465 mm; CP5525dn: 544 x 58 n: 995 x 767 x 822 mm; CP5525dn: 595 x 767 x 87 prices of the state of the	Il Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher II Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types terp, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 144 kg	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see lp, Up arrow, Down arrow); 3 LED status lights (standby), 19.5 watts (sleep), 0.5 watts (manual-off).			
Minimum system requirements  Software  Control panel  Printer management  Power  Dimensions (w x d x h)	Edition, Server 200. http://www.novell.co/ptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.co/www.micross.http://www.micross.http://www.apple.co/print drivers and ins 5.2 cm, 4-line colou (Attention, Data, Re-quirements: Input Typical electricity co. Out of package: CP Packaged: CP5525: Out of package: CP5525: Operating temperat	33-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high officom system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7 is valy); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (possumption (TEC) 5.644 kWh/Week PS525n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 n: 995 x 767 x 82 PS525sn: 53.3 kg; CP5525dn: 35.3 kg; CP5525xh: 88 kg; CP5525th: 168 kg ture: 15 to 27° C. Recommended operating temperat	all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/cljcp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heur USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg	st to the Internet, see support flyer that came in printer at), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see slp, Up arrow, Down arrow); 3 LED status lights			
Minimum system requirements  Software Control panel  Printer management Power  Dimensions (w x d x h)  Weight  Operating environment	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.com/server 200. (Attention, Data, Requirements: Input Typical electricity com/server 200. out of packages: CP Packaged: CP55251. Out of packages: CP Packaged: CP55251. Operating temperature Storage temperature	33 32-bit and 64-bit, Citrix® and Windows® Termina com/iprintl); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mic 3 32-bit and 64-bit, Citrix® and Windows® Termina com/iprintl); Mac OS X v10.4 or higher; Linux (see how Vista®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF sur, graphical and text, LCD control panel display; 7 in early); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (possumption (TEC) 5.644 kWh/Week PS525n: 544 x 586 x 465 mm; CP5525dn: 544 x 586 x 465 mm; CP5525dn: 544 x 586 x 465 mm; CP5525sn: 546 x 822 mm; CP5525sn: 53.3 kg; CP5525h: 8 n: 85 kg; CP5525n: 85 kg; CP5525h: 86 kg; CP5525xh: 168 kg; Linux 10 to 90% RH. Noie	all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/cljcp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heur USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see lp, Up arrow, Down arrow); 3 LED status lights (standby), 19.5 watts (sleep), 0.5 watts (manual-off).			
Minimum system requirements  Software Control panel  Printer management Power  Dimensions (w x d x h)  Weight  Operating environment	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.com/server 200. http://www.novell.com/server/	332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mica 332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see how vista®; Microsoft® Windows® XP SP2 or high offi.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7- iprady); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (nonsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 586 x 465 mm; CP5525dn: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 825	all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types http://www.hplip.net); UNIX, SAP device types http://www.hp.com/support/cljcp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types ter, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heur USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see dware system requirements, see System compatible hardware system requirements, see lp, Up arrow, Down arrow); 3 LED status lights (standby), 19.5 watts (sleep), 0.5 watts (manual-off).			
Minimum system requirements  Software Control panel Printer management Power  Dimensions (w x d x h)  Weight  Operating environment	Edition, Server 200. http://www.novell.cOptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cWindows® 7; Winn http://www.microschitp://www.microschitp://www.apple.cPrint drivers and ins 5.2 cm, 4-line colou. (Attention, Data, Requirements: Input Typical electricity cc Out of package: CP5525; Out of package: CP52525; Out of package: CP52525; Operating temperature Acoustic Pressure E	332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at the and 64-bit; Windows Vista® 32-bit and 64-bit; Windows Vista® 32-bit and 64-bit; Mindows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF in graphical and text, ICD control panel display; 7 jury (stab); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (nonsumption (TEC) 5.644 kVh/Week (nonsumption	all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hp.com/support/clipc5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types terr, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 44 kg ture: 17 to 25° C. Operating humidity: 10 to 70% Rt se level per ISO 9296: Sound power: LwAd6.6 B(A)	s to the Internet, see support flyer that came in printer or, Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see discovered by the system requirements, see System compatible hardware system requirements, see System compatible hardware system requirements, see significant of the system of th			
Minimum system requirements  Software Control panel  Printer management Power  Dimensions (w x d x h)  Weight  Operating environment  Acoustics	Edition, Server 200. http://www.novell.cOptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cWindows® 7; Winn http://www.microschitp://www.microschitp://www.apple.cPrint drivers and ins 5.2 cm, 4-line colou. (Attention, Data, Requirements: Input Typical electricity cc Out of package: CP5525; Out of package: CP52525; Out of package: CP52525; Operating temperature Acoustic Pressure E	332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mica 332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see how vista®; Microsoft® Windows® XP SP2 or high offi.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, LCD control panel display; 7- iprady); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (- 10/+ 6%), 50/60 Hz (nonsumption (TEC) 5.644 kWh/Week P5525n: 544 x 586 x 465 mm; CP5525dn: 544 x 586 x 465 mm; CP5525dn: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 825	all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hp.com/support/clipc5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher all Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types terr, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating P PCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watts 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 44 kg ture: 17 to 25° C. Operating humidity: 10 to 70% Rt se level per ISO 9296: Sound power: LwAd6.6 B(A)	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see discovered by the system requirements, see System compatible hardware system requirements, see System compatible hardware system requirements, see significant or system requirements, see significant system (see p. 19.5). The system compatible hardware system requirements, see system requirements, s			
Minimum system requirements  Software Control panel Printer management Power  Dimensions (w x d x h)  Weight  Operating environment  Acoustics	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.microschttp://www.microschttp://www.microschttp://www.microschttp://www.apple.chttp://ww	33-2-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Visto® 32-bit and 64-bit; Mici 33-2-bit and 64-bit, Citrix® and Windows® Termina (33-2-bit and 64-bit, Citrix® and Windows® Termina (34-bit); Mac OS X v10.4 or higher; Linux (see hows Visto®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF sur, graphical and text, LCD control panel display; 7-jacdy); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (possumption (TEC) 5.644 kWh/Week PSS25n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 n: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 8: PSS25n: 53.3 kg; CP5525h: 8 n: 85 kg; CP5525n: 85 kg; CP5525h: 8 n: 85 kg; CP5525h: 85 kg; CP5525h: 168 kg ture: 15 to 27° C. Recommended operating temperate: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi: issions: 49 dB(A) is: IEC 60950-1 (International); EN 60950-1+A11 (EU 006/95/EC with CE Marking (Europe); other safety	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/support/clicp5525. If no acces http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher II Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types lear, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PPLC 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watt 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 44 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R1 see level per ISO 9296: Sound power: LwAd6.6 B(A) upprovals as required by individual countries	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see subware system requirements, see System compatible hardware system requirements, see slp, Up arrow, Down arrow); 3 LED status lights (standby), 19.5 watts (sleep), 0.5 watts (manual-off).  1. Recommended operating humidity: 30 to 70% RH.			
Minimum system requirements  Software  Control panel  Printer management  Power  Dimensions (w x d x h)  Weight	Edition, Server 200. http://www.novell.coptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cohttp://www.novell.cohttp://www.novell.cohttp://www.microschttp://www.microschttp://www.microschttp://www.microschttp://www.apple.chttp://ww	332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Vista® 32-bit and 64-bit; Mica 332-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hows Vista®; Microsoft® Windows® XP SP2 or high officom system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF ur, graphical and text, ICD control panel display; 7 ji aday); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+ 6%), 50/60 Hz (onsumption (TEC) 5.644 kWh/Week PS525n: 544 x 586 x 465 mm; CP5525dn: 544 x 586 x 95 mm; CP5525dn: 547 x 822 mm; CP5525dn: 995 x 767 x 822 mm; CP5525dn: 33.5 kg; CP5525xh: 8 n: 85 kg; CP5525ch: 85 kg; CP5525xh: 168 kg ture: 15 to 27° C. Recommended operating temperate: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi: isissions: 49 dB(A) :: IEC 60950-1 (International); EN 60950-1+A11 (EL	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/support/clicp5525. If no acces http://www.hp.com/support/clicp5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher II Services (see whitepapers at http://www.hp.com/sttp://www.hplip.net); UNIX, SAP device types lear, Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher; Operating PPLC 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watt 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 44 kg ture: 17 to 25° C. Operating humidity: 10 to 70% R1 see level per ISO 9296: Sound power: LwAd6.6 B(A) upprovals as required by individual countries	s to the Internet, see support flyer that came in printer or), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see subware system requirements, see System compatible hardware system requirements, see slep, Up arrow, Down arrow); 3 LED status lights as (standby), 19.5 watts (sleep), 0.5 watts (manual-off).  1. Recommended operating humidity: 30 to 70% RH.			
Minimum system requirements  Software Control panel  Printer management Power  Dimensions (w x d x h)  Weight  Operating environment  Acoustics	Edition, Server 200. http://www.novell.cOptional: Latest driv box Windows® 7 32-bit Edition, Server 200. http://www.novell.cWindows® 7; Winchttp://www.microschttp://www.microschttp://www.microschttp://www.apple.cPrint drivers and ins 5.2 cm, 4-line colou (Attention, Data, Requirements: Input Typical electricity cc Out of package: CP Packaged: CP5525: Out of package: CP Packaged: CP5525: Operating temperature Acoustic Power Emi Acoustic Power Emi Acoustic Pressure E Safety certifications: Voltage Directive 20 EMC certifications:	33-2-bit and 64-bit, Citrix® and Windows® Termina com/iprint); Mac OS X v10.4 or higher; Linux (see hovers for all supported operating systems available at t and 64-bit; Windows Visto® 32-bit and 64-bit; Mici 33-2-bit and 64-bit, Citrix® and Windows® Termina (33-2-bit and 64-bit, Citrix® and Windows® Termina (34-bit); Mac OS X v10.4 or higher; Linux (see hows Visto®; Microsoft® Windows® XP SP2 or high off.com system requirements; 220 MB available hard com; 150 MB free hard disk space stallation software on CD: Windows® print driver (HF sur, graphical and text, LCD control panel display; 7-jacdy); Enhanced help with animated graphics; Walk-Status Notification Pop-up (SNP) for domains less that voltage: 220 to 240 VAC (-10/+6%), 50/60 Hz (possumption (TEC) 5.644 kWh/Week PSS25n: 544 x 586 x 465 mm; CP5525dn: 544 x 5 n: 995 x 767 x 822 mm; CP5525dn: 995 x 767 x 8: PSS25n: 53.3 kg; CP5525h: 8 n: 85 kg; CP5525n: 85 kg; CP5525h: 8 n: 85 kg; CP5525h: 85 kg; CP5525h: 168 kg ture: 15 to 27° C. Recommended operating temperate: 0 to 35° C. Storage humidity: 10 to 90% RH. Noi: issions: 49 dB(A) is: IEC 60950-1 (International); EN 60950-1+A11 (EU 006/95/EC with CE Marking (Europe); other safety	Il Services (see whitepapers at http://www.hp.com/sttp://www.hp.com/sttp://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types http://www.hplip.netl; UNIX, SAP device types http://www.hp.com/support/clipc5525. If no acces crosoft® Windows® XP 32-bit or 64-bit (SP2 or higher a Services (see whitepapers at http://www.hp.com/sttp://www.hplip.netl; UNIX, SAP device types etc., Server 2003, Server 2008; OS Compatible hard disk space, Mac OS X v10.4 or higher, Operating PPCL 6 discrete), SNP alerts, Mac print driver ob control buttons (Menu, Select, Stop, Back/Exit, Heup USB port with cover in 100 users +/- 2 Hz). Consumption: 620 watts (active), 62 watt 86 x 465 mm; CP5525xh: 745 x 688 x 885 mm 22 mm; CP5525xh: 979 x 797 x 1359 mm 14 kg  Ture: 17 to 25° C. Operating humidity: 10 to 70% RI see level per ISO 9296: Sound power: LwAd6.6 B(A)  UI); IEC 60825-1+A1+A2; GS License (Europe); EN 6 approvals as required by individual countries A, EN 61000-3-2: 2006, EN 61000-3-3: 1995+A1	s to the Internet, see support flyer that came in printer at), Server 2008 32-bit and 64-bit, and 2008 R2 go/upd, Documentation tab); Novell® (see alware system requirements, see System compatible hardware system requirements, see:  July p. Up arrow, Down arrow); 3 LED status lights  s (standby), 19.5 watts (sleep), 0.5 watts (manual-off).  H. Recommended operating humidity: 30 to 70% RH.  0825-1+A1+A2 (Class 1 Laser/LED Device); Low  +A2, EN 55024: 1998+A1+A2, FCC Title 47 CFR,			

http://www.hp.com/uk http://www.hp.com/go/cljcp5525









