

7106



Tally
DASCOM

High Performance Desktop Printer

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

TallyDascom's 7106 direct thermal printer offers reliability, precision and performance in desktop size, where space is limited.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media loading. The clear panel enable simple and effective operation making it very simple to use.

The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

The 7106 offers a wide range of features and options usually only found on high performance machines. For example, it has an internal power supply providing the most reliable operation and avoiding problems usually associated with external power supplies.

The 7106 is easily integrated into existing systems, internal Ethernet interface is also available. In addition to this, the 7106 is also available with options such as a cutter and a peeler to meet industry requirements.

Available Configuration:

7106 Standard Product

7106

Print Speed	6 ips
Print Width	4.10 inches, 104.1 mm
Print Method	Direct Transfer
Print Length	0.25" to 32" (6.35mm to 812,8 mm)
Resolution	203 dpi:
Font Bitmapped	7 styles, True Type
Printhead Life	50 km or 6 months
Memory	16 Mb SDRAM; 4 Mb Flash
Standard Connectivity	Serial (RS-232C), USB (Version 1.1)
Optional Connectivity	Ethernet LAN (10/100 BaseT), Parallel (IEEE-1284)
Standard Emulation	Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus
Consumables	Thermal direct paper and label
Media Width	0.77" to 4.65" (19.6 mm to 118.1 mm)
Media Length	0.25" to 32" (6.35mm to 812,8 mm)
Roll Diameter	Internally: 5" (125 mm) . Externally 8" with optional holder. Core size 1" - 3" (25 mm to 76 mm).
Indexing	Fully adjustable rear sensor and high resolution front sensor
Barcodes	Standard barcodes include: Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxicode, DataMatrix, QR Code, RSS, TLC39
Physical Weigth	3.6 kg
Physical Size	(HxWxD): 183x231x289
Power Voltage	220-240VAC, 50-60Hz
Power Consumption	max 12,9W in Standby, 196W in Operating
Drivers	Windows XP, 2003, Vista, Win 7 (32/64 Bit)
Temperature	+5°C to +35°C
Humidity	30% to 80% (not condensing)
Acoustic	<58dB(A) (ISO 7779)
Options	Auto Cutter, Peeler, Parallel and LAN Interfaces
Note	Accessories Supplied: Head cleaning pen, Start-Up Guide, CD including: Manuals, Drivers and EasyConfig Tool

DASCOM Europe GmbH
Heuweg 3 • 89079 Ulm
Tel.: +49 731 2075-0 • Fax: +49 731 2075-563
info@dascom.com • www.dascom.com

All company and product names are trademarks or registered trademarks of their respective owner.
Copyright © 2010 DASCOM.
Specifications are subject to change without notice.

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS

7106 Provisional Datasheet
Ver. 1.5 / 25.08.2010
Provisional and subject to
change